McCULLOCH CORPORATION
SERVICE BULLETIN

1490

MODEL: Various August 27, 1970

SUBJECT: PARTS CHANGES AND ADDITIONS

Starter rope for the Power Mac 6 saw is now available in 100 foot (reel) lengths under P/N 84338. This and other size rope sold in 100 foot lengths are listed below.

Part No.	Rope Diameter	Manufacturer's Suggested List Price	Models Used On
84338	0.125 inch	$ 9.50	PM 6, MM 6
36825	0.156 inch	$ 11.95	MAC 10, Etc.
28902	0.188 inch	$ 13.15	250,550,S797, CP-125, etc.

* *

Current production units of the Model CP-125 saw are equipped with Spark Plug, P/N 63432 (AC CS 42T). This is a colder plug than the P/N 63097 (AC CS 45T) previously used on the CP-125 although listed as an alternate in the Illustrated Parts List. Under extremely hot operating conditions we recommend the use of an AC CS 41T, P/N 65778, which is a colder heat range plug than the AC CS 42T.

* *

All Throttle Shaft Assemblies, P/N 67486, shipped from the factory from this date will have a throttle plate recess in the shaft measuring 0.850 inch. This will permit Throttle Shaft Assembly, P/N 67486, to be used on all McCulloch SDC carburetors for the MAC 10 Series, CP-55, CP-70, etc., and including such as Carburetor Assembly, P/N 67379, with a 5/8 inch bore, or Carburetor Assembly, P/N 69442, with a 3/4 inch bore.

Throttle Shaft Assemblies, P/N 67486, having an 0.800 inch recess can only be used on carburetors with a 5/8 inch bore.

* *

Please refer to the Illustrated Parts List, P/N 83199, covering the Power Mac 6 saw. See Figure 3, page5 , and note the following correction to the parts list. Item Nos. 15 and 30 are reversed and should be corrected to read as follows:

Item No. 15 - Part No. 83187
Item No. 30 - Part No. 83185

McCULLOCH CORPORATION

By Jack Carroll
Service Manager

Copyright 1970 by McCulloch Corporation

LITHO IN U.S.A.