McCULLOCH CORPORATION
SERVICE BULLETIN

1553

MODEL: Various

April 15, 1974

SUBJECT: FIXED HIGH SPEED JET CARBURETORS

All Pro Mac (PM) and Super Pro (SP) models in current production are equipped with fixed high speed jet carburetors. The standard jet installed in the carburetor at time of shipment is suitable for operations in an altitude range of sea level to 4000 feet. Alternate size jets are available for altitudes above the standard range. Models, carburetors, altitude ranges and jet sizes are summarized below.

Model	Carburetor P/N	Altitude Range	Jet Size	Jet P/N	Manufacturer's Suggested List Price
PM 55	89324	0 to 4000 ft. (0 to 1220 meters)	32	90346	$ 1.10
PM 60	89324	3000 to 5500 ft. (915 to 1677 m)	31	90348	1.10
		4500 to 8000 ft. (1372 to 2439 m)	29	90349	1.10
		7000 ft. and Up (2134 m and Up)	28	90350	1.10
SP 60	89869	0 to 4000 ft. (0 to 1220 meters)	31	90348	1.10
SP 81	89882	3000 to 5500 ft. (915 to 1677 m)	29	90349	1.10
		4500 to 8000 ft. (1372 to 2439 m)	28	90350	1.10
		7000 ft. and Up (2134 m and Up)	26	90351	1.10
PM 105	86285	0 to 4000 ft. (0 to 1220 meters)	038	90430	.80
895	86285	3000 to 5500 ft. (915 to 1677 m)	037	84059	.80
		4500 to 8000 ft. (1372 to 2439 m)	036	90429	.80
		7000 ft. and Up (2134 m and Up)	035	90427	.80
SP 105	87288	0 to 4000 ft. (0 to 1220 meters)	029	88771	2.25
SP 125C	87288	3000 to 5500 ft. (915 to 1677 m)	028	88772	2.25
		4500 to 8000 ft. (1372 to 2439 m)	027	88781	2.25
		7000 ft. and Up (2134 m and Up)	026	88780	2.25

McCULLOCH CORPORATION

By Jack Carroll
Director, Product Service

Copyright 1974 by McCulloch Corporation

LITHO IN U.S.A.